

ORDERING GUIDE

EXAMPLE: 8", FIGURE #83 90 0-BC-1

83	90	0	-	BC	-	1
1.	2.	3.		4.		5.

8" CLASS 900 API 6D FULL OPENING SWING CHECK VALVE, RF FLANGED,
A216 WCB BODY/CAP, 316 SS TRIM, HNBR O RINGS, NACE MR-0175.

1. MODEL

83 – API 6D SWING CHECK VALVE REPLACEABLE SEAT
84 – API 6D SWING CHECK VALVE INTEGRAL SEAT

2. RATING

15 – CLASS 150	90 – CLASS 900
30 – CLASS 300	150 – CLASS 1500
60 – CLASS 600	250 – CLASS 2500

3. END CONNECTION

0 – RF FLANGED	9 – RING JOINT
7 – BUTTWELDED (SCHEDULE REQUIRED)	X – SPECIAL
8 – BUTTWELDED X RF FLANGED	

4. MATERIAL (BODY + COVER) + TRIM

BC – WCB + 316	GC – LCC + 316
DC – WCB + 13CR (410 SS)	LC – CF8M + 316
FC – LCC + 13 CR (410 SS)	X – SPECIAL

5. MATERIAL (O RING)

1 – HNBR	5 – AFLAS
2 – VITON-B	6 – BUNA – N
3 – VITON – GLT	7 – METAL TO METAL
4 – EPDM	8 – SPECIAL

6. SPECIAL REQUIREMENTS

O – OUTSIDE WEIGHT & LEVER
S – SUPPLY COMPLETE INFORMATION