


ORDERING GUIDE

Example: 4” Figure B150-1-BC-G2-L



4” CLASS 150 FLOATING BALL VALVE, FLG-RF, FULL BORE, A216 WCB BODY x 316SS TRIM, RPTFE SEAT, FKM (VITON) AED O-RINGS, NACE, FIRESAFE, LEVER OP

1. MODEL

B - FLOATING BALL, SPLIT BODY, FULL BORE
 C - FLOATING BALL, SPLIT BODY, REDUCED BORE

2. RATING

15 - CLASS 150	90 - CLASS 900 *	*1/2” -2” Sizes Only
30 - CLASS 300	150 - CLASS 1500 *	**1/2”-1.5” Sizes Only
60 - CLASS 600	250 - CLASS 2500 **	

3. END CONNECTION

0 - RF FLANGED	9 - RING JOINT
7 - BUTTWELD (SCHEDULE REQUIRED)	X - SPECIAL

4. TYPE

1 - FIRE-SAFE

5. MATERIAL (BODY + TRIM)

AC - WCB + 304	FC - LCC + F6A/13CR	LF - F316/F316L + 316/316L
AF - A105 + 304	FF - LF2 + F6A/13CR	MC - CF3 + 304L
BC - WCB + 316	GC - LCC + 316	NC - CF3M + 316L
BF - A105 + 316	GF - LF2 + 316	PC - A890-4A + F51
CC - WCB + A105/ENP (.003)	HC - LCB + LF2/ENP (.003)	PF - F51 + F51
CF - A105 + A105/ENP (.003)	IC - LCB + F6A/13CR	QF - F60 + F60/ENP (.003)
DC - WCB + F6A/13CR	JC - LCB + 316	RF - F60 + F51
DF - A105 + F6A/13CR	KC - CF8 + 304	X - SPECIAL
EC - LCC + LF2/ENP (.003)	KF - F304/F304L + 304/304L	
EF - LF2 + LF2/ENP (.003)	LC - CF8M + 316	

6. MATERIAL (SEAT)

G - RPTFE	V - PEEK	X - SPECIAL
B - NYLON	J - DELRIN	

7. MATERIAL (O-RING SEAL)

1 - HNBR AED	4 - EPDM	X - SPECIAL
2 - FKM (VITON) AED	5 - AFLAS	
3 - FKM (VITON) GLT AED	6 - HNBR LT AED	

8. OPERATOR

L - LEVER OPERATOR	GO - WORM GEAR OPERATOR	B - BARE STEM
--------------------	-------------------------	---------------

9. SPECIAL REQUIREMENTS

EB - EXTENDED BONNET	S - SUPPLY COMPLETE INFORMATION
----------------------	---------------------------------